

U-TP 9000C

Boarding Pass & Baggage Tag Printer



U-TP 9000C is a high-speed and space-efficient printer for boarding pass and bag tag, comprising a boarding pass printer (BPP) and baggage tag printer (BTP) in one device. It has a multi-printing function that allows group issuance which makes it faster to print boarding passes and baggage tags for a large number of passengers simultaneously. With a compact size compared to the previous version, it saves more space at check-in counters.

Efficiency of the check-in counter tasks and reasonable price for airports	Providing a perfect interface with the common-use passenger processing system	Creating a new work environment that is convenient and user-friendly	Multi-printing function for nonstop work processing, and reduction of maintenance cost
--	---	--	--

U-TP 9000C

PRINT METHOD	Direct line thermal	
SUPPORTED COMMANDS	AEA2019	
CERTIFICATION	CUPPS (IIAC AirCUS, ARINC vMUSE/iMUSE/cMUSE, SITA CUTE/Liaison etc.)	
INSTALLATION ENVIRONMENT	Power	Operating: Max. 150W / Stand-by: Max. 5W
	When Operating	5 ~ 40°C / 30 - 85%RH, Alarm buzzer, Altitude: 0~5,000m
	When Being Stored	-5 ~ -50°C / 5 - 95%RH
RESOLUTION	203dpi	
IATA RESOLUTION	722e, 740, 1740e (fully compatible with ITPS)	
RELIABILITY	Thermal head	150km
	Boarding Pass	500,000 cuts (auto-cutter)
	Baggage Tag	1,000,000 tags (auto-cutter)
CHARACTER CODES	Single-byte	Latin (Default), Cyrillic
	Double-byte	Chinese (GB18030) , UTF-8
CHARACTER SIZE	The height and width is adjustable by BTT(PECTAB) command. Single-byte character code obeys the specified value of the size (HxW). Double-byte code determines the size from the specified value scope.	
BARCODE TYPE	1-DIMENSIONAL	Code Interleaved 2of5, Code Industrial 2of5, Code 39, Code 128, EAN 13
	2-DIMENSIONAL	PDF417, QR code, Aztec, Data Matrix
INTERFACES	USB 2.0 (Supporting virtual communication for RS232C)	
AUTO CUTTER	Full cut (Guillotine Method)	
PRINTER MODULE	Printer Line Width	80mm
	Printing Speed	5, 6, 7, 8 inch/sec (selectable)
	Printing Concentration	Adjustable in 40 levels
POWER CONSUMPTION	Stand-by power	Below 10W
	Operating power	Below 130W
OPERATING TEMPERATURE	5 to 40°C (-5 to 50°C when stored)	
OVERALL DIMENSIONS	190.0(W) × 620.1(D) × 658.2(H) mm	
WEIGHT	Approximately 36.9kg	
OPTION	RFID Unit (supporting UHF)	